






AV1300 Gigabit Passthrough Powerline Starter Kit

Smooth Ultra HD Streaming
in Every Room



TL-PA8033P KIT



Highlights

HomePlug AV2 Standard Compliant

The HomePlug AV2 standard creates high-speed data transfer rates of up to 1300Mbps to support all your online activities.



Gigabit Ethernet for Fast Connections


Gigabit Ethernet port provides reliable high-speed wired connections for game consoles, smart TVs, STB and more.



Highlights


2 x 2 MIMO for More Throughput over Powerline

2 x 2 MIMO technology is like adding an extra lane on a highway. It establishes multiple simultaneous connections so you can enjoy 2x speeds and greater stability.



Internet from Any Outlet

AV1300 3-port Gigabit Passthrough Powerline Starter Kit brings internet to any area with a power outlet using your home's electrical wiring.



Features

Speed

- **Ultra-fast Powerline Speed** – HomePlug AV2 standard compliant, high-speed data transfer rate of up to 1300Mbps, ideal for Ultra HD streaming and online gaming
- **Gigabit Ports** – Gigabit Ethernet ports allow your TVs, game consoles or PCs to connect to the internet at high speeds

Ease of Use

- **Plug, pair and play** – Plug, pair and play, no configuration required
- **No new wires** – No new wires, use existing electrical wiring to expand your home network
- **Keep your outlet** – An integrated socket lets you power regular devices as normal, and a built-in noise filter prevents them from interrupting the powerline signal
- **TP-Link tpPLC** – Allows you to easily manage your network using the tpPLC Utility

Range

- **300-meter Range** – Up to 300-meter range over the household power circuit

Security

- **Pair Button** – 128-bit AES encryption easily at a push of the "Pair" button

Reliability

- **Mains Filter** – Mains Filter inside the outlet reduces electrical noise interference and improves powerline communication performance


Energy Saving

- **Power Saving** – Power Saving Mode helps reducing power consumption by up to 85%

Specifications

Hardware

- Plug Type: EU
- Standards and Protocols: HomePlug AV2, HomePlug AV, IEEE 1901, IEEE 802.3, IEEE 802.3u, IEEE 802.3ab
- Power Consumption: Maximum: 5.53W
Typical: 5.32W
Standby: 1.36W
- Range: 300 meters over electrical circuit
- Interface: Gigabit Ethernet Ports, Power Socket
- Button: Pair Button
- LED Indicator: Power, Powerline, Ethernet
- Dimensions (W x D x H): 2.8 x 1.7 x 5.2 in. (71 x 42 x 131 mm)



For more information, please visit
<http://www.tp-link.com/en/products/details/TL-PA8033P-KIT.html>
or scan the QR code left

* Compatible with all HomePlug AV & AV2 Standard Powerline adapters.

* Listed HomePlug AV2 speeds refer to the theoretical maximum physical-layer data transfer rate. Actual data speeds vary and are influenced by the home's electrical/physical environment, and if adapters are placed on the same home circuit. Specifications are subject to change without notice. TP-Link is a registered trademark of TP-Link Technologies Co., Ltd. Other brands and product names are trademarks or registered trademarks of their respective holders. Copyright ©2018 TP-Link Technologies Co., Ltd. All rights reserved.

Software

- Modulation Technology: OFDM (PLC)
- Encryption: Powerline Security: 128-bit AES

Others

- Certification: CE, RoHS
- Package Contents:
Powerline Adapter TL-PA8010P, TL-PA8030P
2 × Ethernet Cable
Quick Installation Guide
- System Requirements:
Windows 2000/XP/2003/Vista, Windows 7/8/8.1/10, Mac, Linux
- System Requirements for tpPLC Utility:
Windows XP/Vista/7/8/8.1/10 and Mac OS X (10.7 or later)
- Environment:
Operating Temperature: 0°C~40°C (32°F ~104°F)
Storage Temperature: -40°C~70°C (-40°F ~158°F)
Operating Humidity: 10%~90% non-condensing
Storage Humidity: 5%~90% non-condensing