



Model

# GS 1028PS2

24-Port Gigabit POE+ Switch  
with 2 Gigabit SFP Port



Datasheet



## Features

- 24\*10/100/1000M POE ports +2\* Gigabit SFP Uplink Port;
- Comply with IEEE 802.3, IEEE 802.3u, IEEE802.3ab ,IEEE802.3z IEEE802.3x standards;
- Ethernet port supports 10/100/1000M adaptive;
- Flow control mode: full-duplex adopts IEEE 802.3x standard, half-duplex adopts Back pressure standard;
- Support port auto flip (Auto MDI/MDIX);
- Automatically supplied to adaptive devices;
- Panel indicator monitoring status and help failure analysis;
- Support for VLAN mode, Default mode and Extend mode;
- 1 U 19 inch rack installation

## Specifications

Power	Input: AC 100-240V, 50/60Hz
Ethernet	24 *10/100/1000M PoE Port 2* Gigabit SFP Uplink Port
Switching Capacity	52Gbps
Throughput	38.68Mpps
Packet Buffer	4Mb
MAC Address	8K
Jumbo Frame	9.6Kbytes
Transfer Mode	Store and forward
MTBF	100000 hour
Network protocol	IEEE802.3 (10Base-T)
	IEEE802.3u (100Base-TX)
	IEEE802.3ab(1000Base-TX)
	IEEE802.3z(1000Base-FX)
PoE Protocol	IEEE802.3af (15.4W)
	IEEE802.3at (30W)
Industry Standard	EMI: FCC Part 15 CISPR (EN55032) class A
	EMS: EN61000-4-2 (ESD)、 EN61000-4-4 (EFT)、
	EN61000-4-5 (Surge)
	Shock: IEC 60068-2-27
	Free Fall: IEC 60068-2-32
	Vibration: IEC 60068-2-6



# Specifications

<b>Network Medium</b>	10Base-T : Cat3、 4、 5 or above UTP(≤100m) 100Base-TX : Cat5 or above UTP(≤100m) 1000Base-TX : Cat5 or above UTP(≤100m)
<b>Optical Media</b>	Multimode fiber : 50/125, 62.5/125, 100/140μm Single mode fiber: 8/125, 8.7/125, 9/125, 10/125μm
<b>Security Certificaes</b>	CE、 FCC、 RoHS
<b>Working Environment</b>	Working Temperature: -20~50°C Storage Temperature: -40~85°C Working Humidity : 10%~90%, non-condensing Storage Temperature: 5%~90%, non-condensing Working Height: Maximum10,000 feet Storage heigh: Maximum 10,000 feet
<b>LED Indicators</b>	PWR (power supply) ,1-26 ACT (Link&Data) , 1-26 1000M (Link)
<b>PWR</b>	Lighting: Powered Un-Light: No Power
<b>1-24 ACT (Link&amp;Data)</b>	Lighting: Connecting Flashing: Data Transmit Un-Light: Disconnect
<b>1-24 1000M (Link)</b>	Lighting: 1000M Un-Light: 10/100M

<b>VLAN</b>	Port isolation mode. In this mode, the PoE ports (1-24) of the switch cannot communicate with each other, and can only communicate with the UP-link port.
<b>Default</b>	Normal mode, all port can communicate with each other, the transmission distance is within 100 meters
<b>Extend</b>	Link extension mode, 17-24 ports PoE power supply and data transmission distance can be extended to 250 meters, the transmission rate becomes 10M
<b>Structure Size</b>	Product Dimension (L*W*H): 440*204*44mm Package Dimension (L*W*H): 500*275*85mm N.W: 2.8Kg G.W: 3.3kg
<b>Packing Info</b>	Carton MEAS: 520*445*300mm Qty: 5 units Weight: 17.5KG
<b>Power Voltage</b>	Input Voltage : AC 100-240 V Power supply: 52V5.76A
<b>Package List</b>	Switch 1 pcs, Power cord 1 pcs, User manual 1 pc, Certification 1 pc, Brackets 1 pair