


Keystone Solarix CAT6 STP RJ45 toolless colour modules



Product number:
25286807

Type number:
SXKJ-6-STP-RAL-SA

EAN barcode:
8595684704914



Key features

- Quality shielded category 6/Class E keystone
- Designed for high-speed ethernet protocols, including 2.5GBASE-T and 5GBASE-T
- Very easy toolless installation without the need of using a cable tie
- Innovative GROUND LOCK mechanism allows for a reliable connection of the keystone shielding with the grounding wire or braid of an installation cable
- The shortened COMPACT HD keystone design is suitable for even the most demanding applications, including modular high-density patch panels and outlets (keystone depth is only 31.9 mm)
- The newly developed SECURE CAP includes an integrated cable stopping feature as well as the T568A and T568B colour wiring schemes
- The keystone meets the ISO/IEC 11801, EN 50173, and ANSI/TIA 568.2-D cabling standards
- The colour of the keystone is black (inner parts) and silver (metal body)
- For better port identification and easier management in the rack, it is possible to choose the colour of the front module of the keystone thanks to its unique RAL FIT system
- A black module is available as default, there are also modules with patch cable colours in the packaging – i.e. red, blue, yellow, green, and grey

Cabling standards and technologies

General standards	EN 50173-1, EN 50173-2, ISO/IEC 11801-1, ISO/IEC 11801-2, ANSI/TIA 568.2-D
Product standards	EN 60603-7-5
Technologies applied	GROUND LOCK, COMPACT HD, SECURE CAP, RAL FIT

Supported protocols

	10BASE-T	100BASE-TX	1000BASE-T	2.5GBASE-T	5GBASE-T
Supported by the SXKJ-6-STP-RAL-SA keystone	YES	YES	YES	YES	YES



Supported PoE

	802.3af	802.3at
PoE type	Type 1	Type 2
Maximum current	350 mA	600 mA
No. of pairs used	2	2
Supported by the SXXJ-6-STP-RAL-SA keystone	YES	YES

Physical parameters

Keystone construction	STP
Number of ports	1 x RJ45 8p8c
Min. port lifetime	1000 connections/disconnections
Contacts plating	50 µin gold
Termination	toolless
Number of terminations	200
Size and type of conductor	AWG 26 – 22, solid wire
Material of non-metallic parts	FR plastic according to UL94-0
Keystone body colour	black (inner parts) and silver (metal body)
Snap-in modules colours	black, red, blue, yellow, green, and grey


Operation and storage

Operating temperature	-10 to 60 °C
Storage temperature	-40 to 70 °C
Max. operating humidity	93%

Logistic parameters

Keystone packaging size (h x w x d)	145 mm x 90 mm x 20 mm, plastic bag
Weight	30 g
Included in the package	1x keystone, 1x plastic SECURE CAP with wiring map, 6x colour RAL FIT modules (black, red, blue, yellow, green, and grey)
Master packaging	280x keystones
Master packaging size (h x w x d)	230 mm x 515 mm x 400 mm, carton box
Batch marking	yes (on the product, its packaging and on the transport master box)
Batch and product numbers barcode	IDAutomation Code 39, ANSI/ISO/AIM specification
EAN code type	EAN-13

Keystone label



Solarix warranties

Standard warranty	5 years
System warranty	30 years



Related products

Product Number	Type Number	Description
26000003	SXKD-6-FTP-PVC	Installation Cable Solarix CAT6 FTP PVC Eca 500m/reel
26000005	SXKD-6-FTP-LSOH	Installation Cable Solarix CAT6 FTP LSOH Dca-s2,d2,a1 500m/reel
27655194	SXKD-6-FTP-PE	Installation Cable Solarix CAT6 FTP PE Fca Outdoor 500m/reel
24000100	SX24M-0-STP-BK-UNI-N	Unloaded Patch Panel Solarix 24 port Black 1U
23100101	SX9-1-0-WH	Solarix Modular Wall Outlet for 1 Keystone, White
23100102	SX9-2-0-WH	Solarix Modular Wall Outlet for 2 Keystones, White
23100103	SX9-3-0-WH	Solarix Modular Wall Outlet for 3 Keystones, White
23100201	SXF-M-1-22,5-WH-P	French Style Module Solarix 22.5 x 45mm for 1 Keystone, 90° White
23100202	SXF-M-1-45-WH-P	French Style Module Solarix 45 x 45mm for 1 Keystone, 90° White
23100203	SXF-M-2-45-WH-P	French Style Module Solarix 45 x 45mm for 2 Keystones, 90° White
23100204	SXF-M-2-45-WH-U	French Style Module Solarix 45 x 45mm for 2 Keystones, 45° White
23100206	SXF-M-1-22,5-WH-U	French Style Module Solarix 22.5 x 45mm for 1 Keystone, 45° White
28420xxx	C6-315GY-yyMB	Patch Cable CAT6 SFTP PVC yy (length) Grey snag-proof
28730xxx	C6-315BU-yyMB	Patch Cable CAT6 SFTP PVC yy (length) Blue snag-proof
28740xxx	C6-315YE-yyMB	Patch Cable CAT6 SFTP PVC yy (length) Yellow snag-proof
28750xxx	C6-315GR-yyMB	Patch Cable CAT6 SFTP PVC yy (length) Green snag-proof
28760xxx	C6-315RD-yyMB	Patch Cable CAT6 SFTP PVC yy (length) Red snag-proof

