

SXKJ-6-UTP-BK-SA



# SOLARIX CATEGORY 6

## Keystone Jacks

2.5/5 Gbps

250 MHz

Number of Ports	1 x RJ45
Life Cycle	1,000 plug insertions
Contact Material	50 µin gold
Termination Block	Dual 110/Krone
Termination Block Life Cycle	200 terminations
Conductor Size and Type	AWG 26 - 22, solid
Other Material	FR according to UL94V-0
Storage Temperature	-40 to +70 °C
Operation Temperature	-10 to +60 °C
Max. Humidity Operation	93 %

These Solarix Category 6 keystone jacks exceed the permanent link and channel requirements defined in the ANSI/TIA 568C.2, ISO/IEC 11801, and EN 50173 standards. The keystones are tested up to 250 MHz and provide a sound platform for supporting all today's network protocols including 2.5/5GBASE-T. These Category 6 keystone jacks can be terminated with 110 as well as Krone termination tools. The Solarix Category 6 keystones feature colour-coding for both T568A and T568B wiring and are very easy to install. Similarly to other Solarix products, the new contact design provide enhanced plug to jack connection integrity. The contacts are rated for 1,000 plug insertions.

### Part No.

### Description


SXKJ-6-UTP-BK

Keystone Solarix CAT6 UTP RJ45 Black

SXKJ-6-STP-BK

Keystone Solarix CAT6 STP RJ45 Black

SXKJ-6-STP-BK



SXKJ-6-STP-BK



+420 840 505 555 • info@solarix.cz  
www.solarix.cz

