

UniFi® SWITCH



UniFi Aggregation Switch

USW-Aggregation is a managed Layer 2 switch with eight 10G SFP+ ports, offering link aggregation for higher capacity and increased availability. USW-Aggregation features Layer 2 capabilities and supports high-bandwidth links, making it ideal for aggregation switching to any UniFi solution that deploys various interconnect topologies. Built-in 36W AC/DC power supply can support copper Ethernet UF-RJ45-10G modules (sold separately) in all eight ports.



Mechanical

Dimensions	442.4 x 120 x 43.7 mm (17.42 x 4.72 x 1.72")
Weight	Without Mount: 2.65 kg (5.84 lb) With Mount: 2.74 kg (6.04 lb)
Enclosure Material	SGCC Steel

Hardware

Total Non-Blocking Throughput	80 Gbps
Switching Capacity	160 Gbps
Forwarding Rate	119.04 Mpps
Max. Power Consumption	30W
Power Method	Universal AC Input: 100-240VAC, 50/60 Hz
Power Supply	AC/DC, Internal, 36W
Management Interface	Ethernet In-Band
Modes	SMB Layer 2 Gigabit Ethernet Switch
ESD/EMP Protection	Air: ± 16kV, Contact: ± 12kV
Operating Temperature	-5 to 40° C (23 to 104° F)
Operating Humidity	10 - 90% Noncondensing
Certifications	CE, FCC, IC



LEDs

System

(1) Bootup Animation: Bootup in Progress
Firmware Upgrade Icon: Firmware Upgrading
Steady White: Factory Defaults, Awaiting Adoption
Steady Blue: Device is Adopted

SFP+

White: 1/10G

