

StarterAdapter™ SMA

ADAPTER WITH TWO RP-SMA FEMALE CONNECTORS

The StarterAdapter™ SMA converts waveguide interface into coaxial RP-SMA for Horizontal and Vertical polarization. Adapter enables using radios with coaxial interface with any StarterDish™ antennas.



TECHNICAL DATA

Antenna Connection	Waveguide Port
Radio Connection	2x RP-SMA female
Materials	Insert - Aluminium Alloy Adapter - UV stabilized and weather resistant ABS plastic
Flame Rating	UL 94 HB
Temperature	-40°C to +60°C (-40°F to +140°F)
Wind Survival	160 km/h
Weight	0.12 kg / 0.26 lbs – single unit 0.16 kg / 0.35 lbs – single unit incl. package 17.0 kg / 37.4 lbs – carton (100 units)
Single Unit	Retail Box: 120 x 75 x 75 mm / 4.7 x 2.9 x 2.9 inch
100 Units	Carton Box: 780 x 410 x 260 mm / 30.7 x 16.1 x 10.2 inch

PERFORMANCE

Frequency Range	5150 - 5950 MHz
Polarization	Dual Linear H + V
VSWR Max	1.8
Impedance	50 Ohm

COMPATIBLE WIRELESS PLATFORMS

RF elements®	any StarterDish™ Antennas
--------------	---------------------------

PRODUCT DIMENSIONS

